




TELE DATA S.r.l.

Via Vincinella 14 - 19035 - S.Stefano M. (SP)

Tel. 0187-632323 Fax 0187-631060

www.tele-data.it

Email: teledata@tele-data.it



POWER SUPPLY BOARD BPW - 01

- Board dimensions: 140x60mm
- 5,08mm pitch terminal Connectors
- INPUT: 24/28Vdc nominal: wide range 18 ÷ 36 / Max 4A
- OUTPUT: ± 13Vdc (±10%) Max 2.5A
- Operating Temperature: - 40°C +85°C
- Storage Temperature: - 55°C +125°C
- Continuous Short Circuit Protection with automatic reactivation
- Input line protection with 5x20mm fuse, fast replacement slot with electrical terminal protection
- Replaceable fuse: ceramic body - T5A - 250V
- Continuous protection against input voltage polarity inversion
- Over Voltage Protection
- I / O Insulation: 1500Vdc
- Input voltage presence luminous signalling
- Output voltages presence luminous signalling

TERMINAL PINOUT

J1 Connector: Electrical supply INPUT

Pin 1: +24/28V
Pin 2: 24/28V return
Pin 3: GND (Chassis Ground)

J3 Connector: Electrical supply OUTPUT

Pin 1: N.C. – not used
Pin 2: +13Vdc
Pin 3: 0V
Pin 4: -13Vdc